

48 Position MULTIVAP® Nitrogen Evaporator

DESCRIPTION

The 48 Position MULTIVAP (Catalog# 11848) is a high temperature dry block unit, designed for optimal sample concentration. This is our most versatile MULTIVAP evaporator, accommodating tubes from 10 to 22 mm OD. This unit comes standard with a needle guide to effortlessly center the distribution manifold over small tubes.

This MULTIVAP includes one set of custom heat block inserts, expertly machined to fit the user's tubes. Not only do these custom inserts ensure proper fit and optimal heat transfer, they also eliminate the need to transfer samples to special evaporation vials. Additional heat block inserts are available for use with other tube sizes, sold in singles (Catalog# NA1801) or as a set of 48 (Catalog# NA1803).

This MULTIVAP combines gentle heating of an aluminum dry block with nitrogen blowdown. Reaching temperatures up to 120°C, this instrument is ideal for labs working with solvents with high boiling points. The nitrogen distribution manifold also has a toggle switch for every row of eight samples. This allows each row to be shut off when not in use, conserving nitrogen.



STANDARD FEATURES

- Adjustable flow meter to conserve nitrogen gas **(0-25 LPM)**
- Digital temperature control maintains user-specified temperature to protect delicate samples
- Toggle switches allow gas to be shut off at each row to conserve nitrogen
- Expertly machined aluminum heat block inserts provide optimal heat transfer to sample tubes **(10-22 mm OD)**
- Needle guide to easily align needles with small test tubes.

OPTIONAL FEATURES

- 220 V wiring harness **(Option Code: -2)**
- Z-Purge/positive pressure purge case **(Option Code: -Z)**
- Acid resistant coating on instrument and needles **(Option Code: -RT)**

48 Position MULTIVAP Specifications	
Heater Type	Dry Block
Instrument Catalog Number	11848
Number of Sample Positions	48
Overall Dimensions (W x D x H)	15.25 x 14 x 22 in 39 x 36 x 56 cm
Test Tube Diameter	10-22 mm OD
Gas Manifold Layout	6 x 8 Array
Center to Center Spacing Between Positions	1.0 in 2.54 cm
Gas Flow Meter	0-25 LPM
Stainless Steel Needles Length and Gauge	4.0 in x 19ga 102 mm x 19ga
Hoist Assembly	Dual Pulley & Band Springs
Built-in Gas Regulator Input	30-110 psi
Heating Device Specifications	
Model Number	9156
Outside Dimensions (W x D x H)	15.25 x 14 x 6.5 in 39 x 36 x 15 cm
Total Wattage	900 W
Temperature Range	30-120 °C
Temperature Controller Type and Controller Accuracy	Digital +/- 2°C